

MODEL NO.	FLOW RATE	BIOLOGICAL MEDIA	TANK HOLDING CAPACITY	MATERIAL OF CONSTRUCTION	SUMP PUMP	POWER REQUIREMENTS	DIMENSIONS LXWXH	SHIPPING WEIGHT
Bio-20D-0M10	0-20 GPM	2304 sq ft	890 Gal.	Marine Aluminum	Standard	230V 1Ph 20 Amp	8' x 4' x 4'	950 lbs.
Bio-20D-1M10	0-20 GPM	2304 sq. ft.	890 Gal.	Stainless Steel	Standard	230V 1Ph 20 Amp	8' x 4' x 4'	950 Lbs.
Bio-25R-0M10	0-25 GPM	3,456 sq. ft.	1434 Gal.	Marine Aluminum	Standard	230V 1Ph 20 Amp	12' x 6' x 4'	1400 Lbs.
Bio-25R-1M10	0-25 GPM	3456 sq. ft.	1434 Gal.	Stainless Steel	Standard	230V 1Ph 20 Amps	12' x 6' x 4'	1400 Lbs.
Bio-35R-0M10	0-35 GPM	6480 sq. ft.	2244 Gal	Marine Aluminum	Standard	230V/ 10/25 Amp	12' x 7' x5'	1900 Lbs.
Bio-35R-1M10	0-35 GPM	6480 sq. ft.	2244 Gal	Stainless Steel	Standard	230V/ 10/25 Amps	12' x 6' x 5'	1900 lbs.
BIO-10-0G10	0-10 GPM				n/a	230 V, 10	20 amps	4' x 6' x 110"
BIO-15-0M10	0-15 GPM				3/4 HP	230V, 10	20 amps	5' x 8' x 110"