

OUR INNOVATIVE FOCUS ITEMS

What's in
a name?

Legacy

Highest Quality,
Strength, Longevity and Innovative.

Legacy, from Spraymart, has the widest selection of premium pressure washer parts and accessories available. Offering innovation, superior workmanship, excellent quality and yet price competitive.

You'll find Legacy throughout our catalog in the following sections:

- Pumps
- Guns
- Hoses
- Couplers
- Filters
- Nozzles
- Accessories
- Detergents

Legacy AP1000 Trigger Guns

The World's most popular and easiest to repair trigger gun!!!



- **PSI: 4500**
- **GPM: 12**
- **Temperature: 300°F**
- 3/8" FPT inlet x 1/4" FPT outlet
- Weight: 19 oz

Part No.	Original No.	Description
9.802-229.0	353010	AP1000
8.710-414.0	353010W	AP1000 Weep
8.704-157.0	109856	Unitized Valve
8.704-158.0	109857	Unitized Valve (Weep)
8.704-159.0	109858	Trigger Seal Kit

Durable Glass Reinforced Handle.



AP-1000 Open Gun

Part No.	Original No.	Description
8.710-396.0	352600	Legacy AP1000 Open Gun

-
- **PSI: 4000**
 - **GPM: 12**
 - **Temperature: 300°F**
 - 3/8" FPT inlet x 1/4" FPT outlet
 - Tubular Flow-Thru internals for high pressure and efficiency
 - Weight: 16.7 oz

Legacy Superlite SS Dual Lance

Superlite stainless steel with nozzle guard.



Dual Lance
w/ Nozzle Guard

- **PSI: 4000**
- **Temperature: 200°F**
- Side handle/ Valve actuator
- Viton seal
- Forged brass valve body
- 1/4" MPT inlet
- 1/8" SS outlet tubing

Part No.	Original No.	Description
8.710-618.0	368160	36" - 37.8 oz
8.710-620.0	368165	72" - 56.0 oz
8.900-781.0	109490	Seal Kit

Legacy Rawhide 1-Wire 4000 PSI Black Hose

Durable wrapped finish outer cover



- **Temperature: 275°F**
- 3/8" ID

Part No.	Original No.	Length	Approx wt lbs	Temp
3/8" Black Hose (wrapped)				
8.739-031.0	158280	50'	12.00	275°
8.739-033.0	158290	100'	23.00	275°

Legacy Rawhide 2-Wire 3/8" Hose



Part No.	Original No.	Length	Temp	Approx wt lbs
3/8" Black Hose (6000 PSI) - Wrapped				
8.739-078.0	159580	50'	275°F	17.00
3/8" BLUE Hose (4500 PSI) - Smooth				
8.739-229.0	154415	50'	275°F	17.00
8.739-231.0	154425	100'	275°F	33.00

Legacy Ultima 2-Wire 5000 PSI Black Hose



- Wrapped

Part No.	Original No.	Length	Temp	Approx wt lbs
3/8" Black Hose				
8.739-224.0	154250	50'	275°F	15.00
8.739-226.0	154290	100'	275°F	28.00

Legacy Quick Couplers



Legacy Brass Couplers give Premium Performance with Economy Price. Legacy Quick Connect Couplings are machined from top grade materials to the same exacting specifications as the high cost performance leaders. We have gone a step further to ensure that Legacy Quick Couplers can withstand high temperature, high pressure and aggressive chemicals by including EPDM o-rings as standard.
Compare the performance-Compare the price!

- SS Band for increased durability (except 1/2 inch)
- 4000 PSI

Part No. MPT	Original No.	Part No. FPT	Original No.	Description
9.802-165.0	331015V	9.802-164.0	331016V	1/4" Socket, Brass Coupler
9.802-169.0	331020V	9.802-166.0	331021V	3/8" Socket, Brass Coupler
8.707-139.0	331115V	8.707-136.0	331116V	1/4" Plugs, Steel, Zinc-plated
9.802-171.0	331120V	9.802-170.0	331121V	3/8" Plugs, Steel, Zinc-plated
8.707-164.0	2-2017	8.709-501.0	331126V	1/2" Plugs, Steel, Zinc-plated
8.707-167.0	2-20181	8.709-455.0	331026V	1/2" Socket, Brass Coupler FPT

Case pricing

Case of 200 Part No. - MPT	Case of 200 Part No. - FPT	Description
8.916-542.0	8.916-538.0	1/4" Socket, Brass Coupler
8.916-541.0	8.916-537.0	3/8" Socket, Brass Coupler
8.916-540.0		1/4" Plugs, Stl, Zinc-plated
	8.916-361.0	1/4" Plugs, Stl, Zinc-plated
8.916-539.0		3/8" Plugs, Stl, Zinc-plated
	8.916-536.0	3/8" Plugs, Stl, Zinc-plated

Stainless Steel Quick Couplers



- Chemical resistant
- 303 stainless steel
- 5500 PSI

Part No. MPT	Original No.	Part No. FPT	Original No.	Description
8.707-110.0	2-2001SS	8.707-103.0	2-2000SS	1/4" Stainless Steel Couplers
8.707-135.0	2-2003SS	8.707-125.0	2-2002SS	3/8" Stainless Steel Couplers
8.707-140.0	2-20051	8.707-138.0	2-20041	1/4" Stainless Steel Nipples
8.707-152.0	2-20071	8.707-144.0	2-20061	3/8" Stainless Steel Nipples

Legacy REVOLUTION Turbo Nozzle



Legacy Revolution Turbo Nozzle is rated for up to 4350 PSI at 185°F. Turning at an astounding 4000 RPM, the Revolution delivers faster and deeper cleaning action for the same price of 3000 PSI rotary nozzles.

Nozzle Part No.	Orig No.	Orifice	PSI
9.302-242.0	374231	3.5	4350
9.302-243.0	374232	4.0	4350
9.302-244.0	374233	4.5	4350
9.302-245.0	374234	5.0	4350
9.302-246.0	374235	5.5	4350
9.302-247.0	374236	6.5	4350
9.302-248.0	374237	7.0	4350
9.302-249.0	374238	10.0	4350

Repair Kit Part No	Orig. No.	Orifice
2.884-972.0	079920	3.5
2.883-824.0	079921	4.0
8.932-953.0	079922	4.5
2.883-823.0	079923	5.0
2.883-822.0	079924	5.5
8.932-956.0	079925	6.5
2.884-974.0	079926	7.0
2.884-975.0	079927	10.0

Legacy 4 & 5 Pack Color Coded QC Nozzle Kits



Made in USA

QC Soap Nozzle included in the 5 pack

1/4" Nozzle Kits. The 5 pack includes one 40 x 65° soap nozzle.

4-Pack: 0°, 25°, 40°, Soap

Part No.	Nozzle Size
8.726-117.0	3.0
9.104-028.0	3.25
8.726-119.0	3.5
8.726-120.0	4.0
8.726-121.0	4.5
8.726-122.0	5.0
8.726-123.0	5.5
8.726-124.0	6.0
8.726-125.0	6.5

5-Pack: 0°, 15°, 25°, 40°, Soap

Part No.	Nozzle Size
9.104-024.0	3.0
9.104-016.0	3.25
8.726-128.0	3.5
9.104-030.0	4.0
8.726-130.0	4.5
8.726-131.0	5.0
8.726-132.0	5.5
8.726-133.0	6.0
8.726-134.0	6.5

OUR INNOVATIVE FOCUS ITEMS

Legacy Individual 1/4" QC Nozzles

Legacy



Made in USA

QC Nozzles

"QC", Color Coded, Hardened Stainless Nozzle, fits most 1/4" quick couplers. Rated for 4000 PSI.

Orifice	0° (Red) Part No	15° (Yellow) Part No	25° (Green) Part No	40° (White) Part No
3.0	8.723-576.0	8.902-482.0	8.902-484.0	8.902-485.0
3.25	8.708-538.0	8.708-539.0	8.708-540.0	8.708-541.0
3.5	8.723-577.0	8.726-104.0	8.708-526.0	8.902-487.0
3.75	8.708-527.0	8.708-528.0	8.708-529.0	8.708-530.0
4.0	8.708-531.0	8.708-532.0	8.708-533.0	8.708-534.0
4.5	8.723-578.0	8.708-535.0	8.708-536.0	8.708-537.0
5.0	8.726-105.0	8.726-106.0	8.726-107.0	8.726-108.0
5.5	8.723-579.0	8.902-492.0	8.708-542.0	8.902-493.0
6.0	8.726-109.0	8.726-110.0	8.726-111.0	8.726-112.0
6.5	8.726-113.0	8.726-114.0	8.726-115.0	8.726-116.0

QC Soap Nozzle



Part No.	Orifice	Degree
8.723-636.0	40	65°

Legacy Compact Foamer

Legacy

Generates a high density clinging foam for extended dwell time to increase chemical action



- Stainless steel, aluminum and brass
- 5" long, 1" diameter
- 4 and 6.5 nozzle included
- 1 to 5 GPM max flow
- 195°F max temperature
- 2500 PSI max pressure

Part No.	Original No.	Description
8.903-998.0	344022V	1/8" F Inlet
8.903-999.0	344023V	1/4" F Inlet

NOTE: Most cleaning chemicals perform best when applied at 120° - 150°F and can be applied as a foam by adding a foaming agent. See your chemical supplier to obtain the correct product.

Brass Chemical Filter

Legacy

50 mesh stainless steel screen. Removable mesh for easy cleaning. Heavy-duty one-piece brass body holds the filter on the bottom of tank.



- 1/4" hose barb
- Stainless steel check ball

Part No.	Original No.	Description
8.903-672.0	340010X	With Check Valve
8.709-934.0	340012X	Without Check Valve

Undercarriage Cleaner

Legacy

- Simply connect to your hot or cold water pressure washer
- Stainless steel rotating assembly built to withstand pressures up to 4000 PSI and 250°F
- Removes road grime, fuel & oil contaminants
- Removes snow sludge & ice
- Provides a clean working environment for technicians
- No more crawling under a vehicle
- Easy to handle & maneuver
- 5.5" Required Clearance
- 7250 PSI Carbon Steel Ball Valve
- 4 Nozzles: (2) 0° #2.0
(2) 25° #2.0



Part No.	Description
8.749-303.0	Undercarriage Cleaner

Cyclone Rotary Surface Cleaner

Legacy



The "Cyclone" rotary surface cleaner can be used with most hot and cold water washers. It reduces overspray and zebra striping. Great for warehouse floors, sidewalks, pool decks, parking lots, etc.

- 4-10 GPM
- 2000 - 3500 PSI
- 200°F
- Polyethylene housing
- Collapsible handle
- Pneumatic tires
- 20" diameter surface cleaning
- Up to 5 gpm
- Weight: 35 lbs

Part No.	Original No.	Description
8.903-608.0	30-587	"Cyclone" Surface Cleaner

Oil-Fired Hot Box

Legacy

Add hot water cleaning economically! Portable water heater add-on for existing cold water pressure washers. Quick Connect to cold water washer, supply fuel and power to Euro-Heat for hot water cleaning applications - USE ONLY WHEN NEEDED and keep the convenience of the portable cold water washer.



- 3000 PSI
- Quick Hookup - 3/8" QC inlet/outlet
- Easy service access to burner parts
- Efficient vertical combustion configuration
- Diesel, Kerosene, #1 Heating Oil
- 10" Easy roll tubed pneumatic wheels
- 5 gallon plastic fuel tank
- Compact size - 37" W x 27" L x 39" H
- 36" Ground Fault Interrupter plug
- Thermostat temperature control

Part No.	Original No.	Description
1.103-910.0	HR-5030D	5 GPM / 3000 PSI - 120V

Legacy HD Pumps — Direct Drive Units



- GS SERIES:**
- 1/2" inlet x 3/8" outlet
 - Direct Couple to Gas Engine
 - PSI: 4000
 - RPM: 3400

Part No.	Model No.	GPM	HP	Shaft	Weight
8.904-972.0	GS4040G.2	4.0	13.0	1" Hollow	24.5 lbs



- GE SERIES:**
- 1/2" inlet x 3/8" outlet
 - NEMA 56C Frame
 - Direct Couple to Electric Motor
 - PSI: 2500
 - RPM: 1725

Part No.	Model No.	GPM	HP	Shaft	Weight
8.916-560.0	GE2825S.1	2.8	5.0	5/8" Hollow	17 lbs

Legacy 500 Flow Switch



Allows for full mounting versatility



- Tough, impact-resistant, glass-reinforced, nylon housing
- Tungsten contact reed switch
- Heavy-duty machine brass internals
- Viton seals
- For solenoid control only
- 1-8 GPM
- 4350 PSI
- 3/8" FPT Inlet / Outlet
- 190°F
- 1 Amp switch
- 2 Wire Reed

Part No.	Original No.	Description
8.712-244.0	410305A	Vertical Mount Only
8.712-247.0	410308A	Mount in Any Position (Gray)
9.803-266.0	109672	Reed Switch Only (2 wire)

Legacy Flow Switch



Spring return float allows full mounting versatility.



- 4050 PSI
- 3500 rated pressure
- Horizontal or vertical mount
- Forged brass body
- 3/8" MPT inlet/outlet
- 8 GPM
- 190°F
- One Amp switch
- Solenoid control

Part No.	Original No.	Description
8.712-246.0	410307P	Flow Switch

Legacy HD Pumps — Belt Drive Units



- GM SERIES:**
- 1/2" inlet x 3/8" outlet
 - PSI: 3500
 - RPM: 1750

Part No.	Model No.	GPM	HP	Shaft	Weight
8.749-938.0	GM6035R.2	5.6	13.5	24 mm	22 lbs

8.749-939.0	GM6035R.2-Left	5.6	13.5	24 mm	22 lbs
-------------	----------------	-----	------	-------	--------



- GM SERIES:**
- 1/2" inlet x 3/8" outlet
 - PSI: 3500
 - RPM: 1500

Part No.	Model No.	GPM	HP	Shaft	Weight
8.904-946.0	GM4035R.2	4.8	7.5	24 mm	22 lbs

Fuel Filter/Water Separator



- 10 micron filtration
- Spin-on convenience
- Water separation chamber
- 1/4" FPT inlet/outlet
- Easy drain water/sediment bowl

Part No.	Description
8.725-306.0	Complete Unit
8.725-307.0	Element

Universal Unloader (UU1)



The Legacy Universal Unloader is unique in that it allows for height and width adjustments making it ideal for any pump. Exclusively available through Spraymart. Patent Pending.



- 6 GPM
- 3500 PSI
- 195°F
- Forged brass body
- 1/2" NPT inlet
- 3/8" NPT outlet
- Stainless steel seat and low-friction, wear-resistant plunger
- 16.1 oz weight

Part No.	Description
9.175-018 .0	Universal Unloader (UU1)

Patent Pending

OUR INNOVATIVE FOCUS ITEMS

Legacy Hose Reels



Fully assembled and ready to use!

Legacy hose reels were designed for ease of use and durability in commercial pressure washer applications.

Offering 100' and 200' reels in both a fixed base and 360 degree rotating base. The oversized reel holds the advertised length plus leaves additional space reducing the difficulty of reeling hose. The unique extended swivel improves the hose connection and reduces hose wear and stress.

Features:

1. Rugged heavy-duty construction for commercial applications.

- Heavy gauge steel fabrication
- Gloss black powder coating
- Easy to use brake mechanism reduces unwinding backlash
- Oversized heavy-duty locking mechanism prevents slippage during reel operation.
- Durable handle

2. "Flip-Over" hose guide: Allows ease of use from either side of the reel

3. Oversized: Oversized to easily fit the advertised length of hose. When we say 100' we mean 100+ feet will easily fit.

4. New swivel design: The reels come with an extended swivel which prevents bends and stress on the hose where it attaches to the reel. Swivels carry a two year warranty.

5. Rotary mount: 360 degree rotation with an oversized heavy-duty locking mechanism. Allows for continual alignment with the hose.

- Mount to round or square tubing

6. Fully assembled: Ready to use out of the box. Saves time and money.

Specifications:

- 5000 psi
- 325°F
- 100' and 200' fixed base
- 100' and 200' 360 degree rotating base
- High pressure double seal swivels.
- Reels equipped for 3/8" hose. Easily convertible to 1/2" hose with the change to a 1/2" swivel.
- 2 year warranty



Part No.	Length	Description
8.750-485.0	100' x 3/8"	Pivot Reel
8.750-482.0	200' x 3/8"	Pivot Reel
8.750-476.0	100" x 3/8"	Fixed Based
8.750-479.0	200" x 3/8"	Fixed Based

NOTE: Hose not included

Command-O Limonene Waterless Hand Cleaner



A unique blend of natural citrus extract "Limonene," Aloe Vera, Glycerine, and Lanolin, plus medication creates COMMAND-O, the world's #1 waterless hand cleaner. COMMAND-O combats the toughest cleaning task including grease, ink, tar, paint, dirt and stains. The conditioning agents protect hands and prevent drying, chapping and cracking.



8.704-634.0



8.704-632.0

Part No.	Original No.	Description
Tool Box Size		
8.704-632.0	112104	7 oz tube (liquid)
8.704-633.0	112105	7 oz tube (liquid with pumice)
Shop Size		
8.704-634.0	112115	1 gallon (liquid)
8.704-635.0	112116	1 gallon (liquid with pumice)
Dispensers		
8.704-636.0	112117	Dispenser Pump (For 1 gallon Jug)

Legacy Electric Motors



TEFC

Part No.	HP	RPM	Shaft Dia	Bolt Circle	Frame/C-Face	Full Load Amps	Voltage
8.750-172.0	1.5	1725	5/8"	5-7/8"	56C	13	115
8.750-173.0	1.5	3450	5/8"	5-7/8"	56C	13	115
8.750-174.0	2.0	1725	5/8"	5-7/8"	56C	18	115
8.750-175.0	2.0	3450	5/8"	5-7/8"	56C	17.5	115



A-Plus is our quality, value-line of pressure washer parts and accessories. High on performance, low on price.

A-Plus is available exclusively at Spraymart. Look for this symbol throughout the catalog:

MV2005 Trigger Gun

Extra value!



- **PSI: 4000**
- **GPM: 8**
- **Temperature: 320°F**
- 3/8" FPT inlet x 1/4" FPT outlet
- Weight: 13.4 oz

Part No.	Original No.	Description
8.710-417.0	353030	MV2005



Adjustable Nozzle

Compact full feature unit weighs only 4.3 oz, same functions as ST-51N.



- 3600 PSI max pressure
- 10 GPM max flow
- 300°F max temperature
- Machined brass body
- Nylon adjustment knob
- 1/4" FPT inlet/outlet

Part No.	Original No.	Description
8.710-891.0	373051P	Adjustable Nozzle



Turbo Nozzles



A+ Revolution Turbo Nozzle is rated for up to 5100 PSI at 212°F. High Impact Nozzle at unbelievable Pricing!

- Forged Brass
- Precision ceramic
- Durable rubber cover



3000 PSI



4000 PSI



5100 PSI

Nozzle Part No.	Orifice
3000 PSI	
8.726-056.0	3.5
8.726-057.0	4.0
8.726-058.0	4.5
8.726-059.0	5.0
8.726-060.0	5.5
8.726-061.0	6.0
4000 PSI	
8.726-068.0	3.5
8.726-069.0	4.0
8.726-070.0	4.5
8.726-071.0	5.0
8.726-072.0	5.5
8.726-073.0	6.0
5100 PSI	
8.726-080.0	3.5
8.726-081.0	4.0
8.726-082.0	4.5
8.726-083.0	5.0
8.726-084.0	5.5
8.726-085.0	6.0

Repair Kit Part No.	Orifice
3000 PSI	
8.726-062.0	3.5
8.726-063.0	4.0
8.726-064.0	4.5
8.726-065.0	5.0
8.726-066.0	5.5
8.726-067.0	6.0
4000 PSI	
8.726-074.0	3.5
8.726-075.0	4.0
8.726-076.0	4.5
8.726-077.0	5.0
8.726-078.0	5.5
8.726-079.0	6.0
5100 PSI	
8.726-086.0	3.5
8.726-087.0	4.0
8.726-088.0	4.5
8.726-089.0	5.0
8.726-090.0	5.5
8.726-091.0	6.0

OUR FOCUS ITEMS

AP Hose Reels

AP hose reels have been designed to perfectly balance ruggedness and durability with affordability.



- Flared flanges for maximum capacity
- Solid center core for maximum strength
- Rolled beaded edge flanges for maximum safety
- Easy mounting options for maximum versatility
- "Posi-Pin" lock, prevents unwanted dereeling
- Heavy-duty powder coated steel
- Easy access external swivel
- 4000 PSI working pressure
- Rated temp: 225°F
- 3/8" or 1/2" Inlet/Outlet

Swivel Repair Kits

Part No.	Original No.
8.900-855.0	110025

Part No.	Original No.	Hose Dia	Capacity (in feet)	Core Width	Flange Width	Flange Diameter	Overall Height
8.711-192.0	386188	3/8"	50	4.3	7.9	10.5	13.0"
9.804-067.0	386191	3/8"	100	8.7	12.2	10.5	13.0"
8.711-199.0	386206	3/8"	150	6.3	10.2	13.0	16.7"
8.711-201.0	386209	1/2"	100	6.3	10.2	13.0	16.7"

NOTE: Hose is not included in price. See page 22 for connector hose.

Stainless Steel Swivels



- Swivels even at 4000 PSI
- 200°F max temperature
- All stainless construction
- Teflon® swivel ring
- Rebuildable
- 3/8" in and out

Part No.	Original No.	Description
8.712-446.0	421016	3/8" MPT x FPT
8.712-447.0	421017	3/8" FPT x FPT
8.900-764.0	109198	Seal Kit
8.900-765.0	109199	Rebuild Kit

Stainless Steel Sewer Nozzles



- 4100 PSI max pressure
- Corrosion Resistant Stainless Steel
- One Forward Orifice
- Three Rear Orifices

Part No.	Original No.	FPT	Size
8.710-905.0	373075	1/8"	5.0
8.710-906.0	373076	1/8"	5.5
8.710-907.0	373077	1/8"	6.0
8.710-908.0	373078	1/4"	6.5
8.710-909.0	373079	1/4"	7.0
8.710-910.0	373080	1/4"	9.5

Water Broom 16"



- 4000 PSI
- Fits any 1/4" wand
- Requires (4) 1/4" nozzles and wand

Part No.	Original No.	Description
8.710-082.0	343615	Water Broom 16"

For best value, look for these and other Legacy and A+ products throughout the catalog

